

SCREEN SIZES:  
43" & 49"

# ROUTE

## DIGITAL LECTURN

Ideal for **retail environments & wayfinding**. Incredibly sleek, stylish and slim yet extremely visible with a choice of sizes; 43" & 49" both with a high bright 700Nit display. Designed to stand out in busy retail and commercial environments.

### PLUG & PLAY (USB) OR CLOUD CMS CONNECTED

Content can be updated easily via USB with the built-in Vestel media player or upgrade to a cloud connected media player to schedule content and schedule remotely.

### VESTEL COMMERCIAL GRADE IPS PANEL

Commercial grade 24/7 operation VESTEL IPS Panel, stylish and slim yet extremely visible with a choice of sizes; 43" & 49" all with a high bright 700Nit display.

### 10 POINT MULTI-TOUCH PCAP GLASS

Utilize a 10 Point PCAP Glass touchscreen with touch screen software, perfect for wayfinding and interactive software.



## FEATURES



CAPACITIVE TOUCH GLASS



INTERNAL LOCKER WITH AV INPUTS



STEREO SPEAKERS



24/7 COMMERCIAL USE


## AVAILABLE ADD-ONS




3G OR WIFI ANTENNA



WINDOWS & ANDROID MEDIA PLAYER



CUSTOM RAL POWDER COATED



VINYL LOGO/FULL BODY WRAP

MADE IN BRITAIN

3 Years Warranty



## FEATURES



### INTERNAL MEDIA PLAYER LOCKER

Built for a wide range of uses, the Lectern Kiosk has a large internal locker for mounting a range of media players from Mirco PC's to Larger Form Factor Players.



### POWERED AMP & SONY SPEAKERS

Built in 210W Sony Speakers for impressive sound and volume quality. Connect to your chosen media player via 2.5mm Aux Jack or Bluetooth.





**SPECIFICATIONS**

	Size	43"	49"
<b>Panel Details</b>	Brightness (Cd / M2)	700	700
	Panel Type	24/7 Panel	24/7 Panel
	Resolution	1920 x 1080 (16:9) – FHD	1920 x 1080 (16:9) – FHD
	Contrast Ratio	1000:1	1200:1
	Dynamic Constrast Ratio	70000:1	70000:1
	Panel Life Time ( Min. )	50000 H	50000 H
	Backlight Type	EDGE TYPE LED	EDGE TYPE LED
	Panel Technology	IPS	IPS
	Viewing Angle	178	178
<b>Audio</b>	Speaker Type	Stereo 2 X 10W, 8Ω	Stereo 2 X 10W, 8Ω
<b>AV Inputs</b>	Video	HDMI,VGA, DVI	HDMI,VGA, DVI
	Audio	Audio Socket(3.5mm)	Audio Socket(3.5mm)
<b>Power</b>	Power Consumption (W)	105 W	95 W
	Input Voltage	AC 100–240V, 50–60 Hz	AC 100–240V, 50–60 Hz
<b>Mechanical</b>	Unit Size (HxWxDmm)	1243 X 1073 x 750 inc Base	1243 X 1173 x 750 inc Base
	Package Size(HxWxDmm)	Pallet Size VERTICAL DELIVERY	Pallet Size VERTICAL DELIVERY
	Net Weight(kg)	47 kg	55 kg
	Gross Weight(kg)	56 kg	64 kg
<b>Environmental</b>	Operating Temperature	0 –40 °C	0–40°C
	Storage Temperature	0 °C to 50 °C	0 °C to 50 °C
	Operating Humidity	–30°C to 60°C	–30°C to 60°C
	Storage Humidity	10% to 80%	10% to 80%
	Regulatory Approvals	CE, FCC, ROHS, HDMI	CE, FCC, ROHS, HDMI